

Description

Monograde lubricant oil developed to cover the needs of low demand 4-stroke petrol engines. Its detergent capacity keeps combustion waste under control, thereby preventing it from being deposited in the engine. As it is made with refined mineral base oils, its carefully studied additives enable oxidation, corrosion and wear of internal engine parts to be controlled.

Properties

- Oil with anti-wear properties.
- Good anti-corrosion properties.
- Low consumption and stable against oxidation thanks to the use of refined and low volatility base oils.

Quality levels, approvals and recommendations

- API SB

Technical specifications

| | UNIT | METHOD | VALUE | |
|---------------------|----------|-------------|----------|----------|
| SAE Grade | | | 40 | 50 |
| Density at 15 °C | g/mL | ASTM D 4052 | 0,892 | 0,897 |
| Viscosity at 100 °C | cSt | ASTM D 445 | 14,9 | 19,1 |
| Viscosity at 40 °C | cSt | ASTM D 445 | 154 | 225 |
| Viscosity index | - | ASTM D 2270 | 95 min. | 95 min. |
| Flash point | °C | ASTM D 92 | 220 min. | 230 min. |
| Pour point | °C | ASTM D 97 | -21 | -18 |
| Sulphated ashes | % weight | ASTM D 874 | 0,1 | 0,1 |

The above mentioned characteristics are typical values and should not be considered product specifications.