PRODUCT INFORMATION



Automotive Chemicals - Technical Sprays - Assembly

Version: TS/030

Valvoline™ Penetrating Oil

High quality pressurized lubricant to loosen rusted parts.

Applications

Screwed connections
Gear wheels
Locks
Fasteners (screws, bolts and nuts)
Tools
Rails
Chains
Garden tools

Product characteristics

Good penetrating properties Contains graphite and MoS2 Moisture repellent Powerful jet spray 360° valve

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ Penetrating Oil should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Apply Valvoline $^{\text{TM}}$ Penetrating Oil and allow it to take effect.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ Penetrating Oil	
Contents	500 ml
Basis	Mineral Oil,
	graphite and
	MoS ₂
VOC-content	Approx. 70%
	w/w
Colour	Graphite/
	Black
Scent	Characteristic
Relative density at 20°C	0,86 g/ml
Yield	2,33 g/sec
Vapour pressure at	3 to 4 bar
20°C	

This information only applies to products manufactured in the following location(s): Europe

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet http://sds.valvoline.com

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces -

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

[™] Trademark of Valvoline, registered in various countries © 2018