

Lubricants – Hydraulic oils

Version: **EEE/197**

Valvoline™ Ultramax HLP 68

Premium hydraulic oil formulated for industrial and earth moving equipment

Ultramax HLP hydraulic fluids are based on highly refined mineral oil and enhanced with a stabilized zinc additive system. For systems working under extreme temperature conditions Valvoline recommends the Ultramax HVLP series.

Performance levels
ISO 11158 HM
DIN 51524 (part 2)
ASTM D6158 HM
Eaton brochure 03-401-2010
Eaton E-FDGN-TB002-E
Bosch Rexroth RDE-90235
Fives Cincinnati P-69
Danieli 0.000.001 Type 11
General Motors LS-2
ZF TE-ML 07H
SWEDISH STANDARD SS 155434
JCMAS HK P041
Parker Denison HF-0, HF-1, HF-2
US Steel 126

Applications

For mobile and static hydraulic applications of industrial and other equipment.

Hydraulic cranes and lifts, loaders, reach trucks, forklifts, excavators, dumpers, loading ramps, and tailboards.

Sometimes recommended as air compressor oil.

*Available in eleven ISO viscosity grades:
5, 10, 15, 22, 32, 46, 68, 100, 150, 220, 320.*

Features & Benefits

Superior performance

The Ultramax HLP range is formulated with premium quality mineral base oils and specially selected additives to guarantee a low pour point, excellent oxidation stability and good flow characteristics.

High resistance to oxidation helps extend service life.

Superior protection

The Ultramax HLP hydraulic oil has a high load-carrying capacity and provides good protection against corrosion, foaming, and sludge building. Good anti-wear performance prevents wear of internal components and reduces downtime.

Consistent viscosity

Good viscosity-temperature properties at average and low temperatures. Stable viscosity over a long period. Available in eleven ISO viscosity grades.

Severe working conditions

Ultramax HLP hydraulic oils can even be used in unfavorable working conditions, like road building and mining or work in damp conditions. The product can handle small quantities of penetrating dust or water and resists foaming, caused by access of air via leaking seals.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

For all latest OEM specifications and approvals visit: www.pisheets.valvoline.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Ultramax HLP 68	
Viscosity, mm ² /s @ 100°C ASTM D-445	9
Viscosity, mm ² /s @ 40°C ASTM D-445	68
Viscosity Index ASTM D-2270	107
TAN, mg KOH/g ASTM D-664	0,6
Pour Point, °C ASTM D-5949	-24
Specific Gravity @ 15.6°C ASTM D-4052	0,880
Flash Point, COC, °C ASTM D-92	220

This information only applies to products manufactured by:

Ellis Enterprises East doo Kruševac,
Affiliate of Valvoline
Mike Stojanovića 15, 37000 Kruševac, Serbia
Registration nr: 21368997 / TIN: 110618744

™ Trademark of Valvoline, registered in various countries

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises East doo Kruševac and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <https://sds.valvoline.com/>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –