

PRODUCT INFORMATION



Automotive Chemicals – Technical sprays - Lubrication

Version: **TS/003**

Valvoline™ White Grease

High quality spray grease to lubricate mechanical parts made of metal or plastic.

Applications

Metal to metal connections
Metal to plastic connections
Door hinges
Springs
Shock absorbers
Roller bearings
Sliding bearings
Ball bearings
Stabilization rubbers
Worm wheels

Product characteristics

Outstanding mechanical and thermal stability
Excellent adhesion properties
Prevents wear and sticking
High viscosity
Resistant to weather influences
Resistant to weak acids and bases
Excellent corrosion prevention
Water-repellent
Contains PTFE (polytetrafluorethylene)
Directed jet spray

Directions for use:

Before use, carefully read the directions on the packaging.

Valvoline™ White Grease should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Apply Valvoline™ White Grease in a thin layer.

Optimum lubrication is reached after evaporation of the solvent.

Keeping the world moving since 1866[™]

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products. For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline [™] White Grease	
Contents	500 ml
Basis	Mineral Oil with EP Grease
VOC-content	Approx. 71% w/w
Colour	Beige
Scent	Characteristic
Appearance	Grease
Relative density at 20°C	0,76 g/ml
Yield	1,51 g/sec
Vapour pressure at 20°C	3 to 4 bar
4 Ball EP-test (ASTM D-2596)	3136 N
4 Ball Wear-test (ASTM D-2266)	< 0,4 mm
Temperature resistant	-30°C to +160°C
pH-value	Neutral

This information only applies to products manufactured in the following location(s): Europe

[™] Trademark of Valvoline, registered in various countries © 2018

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://sds.valvoline.com>

Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces –