



specialty lubricants



Quality is in our nature

Eurol Assembly Paste HT/AL

High temperature assembly paste

Description:

Eurol Assembly Paste HT / AL with Eurol SYNGIS Technology is an anti-seize and extreme pressure lubrication paste for very high temperatures.

Eurol Assembly Paste HT / AL is very suitable for treating and sealing of all types of screw / thread and non-threaded connections in:

- Brakes
- Exhaust systems
- Turbo chargers
- Steel mills
- Refineries
- Cement mills
- Off road / agricultural machines
- Ship building or repair
- Ovens
- Metalworking machines
- Bearings, chains at high temperatures

Instructions for use:

- Remove old assembly paste residue from the thread connection
- Clean thoroughly before application
- Apply a thin layer with a brush

Eurol Assembly Paste HT/AL has the following characteristics:

- Extreme pressure lubrication
- Excellent protection against fretting corrosion
- Very oxidation stable
- Resistant to steam
- For very high temperatures up to +1100°C
- Contains solid lubricants
- For ferrous and non ferrous metals
- Low friction coefficient
- Very economical in use

Physical properties:

Colour	Grey	
NLGI consistency	2	ASTM D 217
Thickener type	Lithium	
Base oil viscosity	100 cSt	ASTM D 445
Flash point	150 °C	ASTM D 93
Operating temperature	-30 - 1100 °C	

Greases - S006250
Version 1.1, 15-01-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com