



specialty lubricants



Quality is in our nature

Eurol Assembly Paste HT/FD Spray

High temperature assembly paste for the food industry

Description:

Eurol Assembly Paste HT/FD with Eurol SYNGIS Technology is a high temperature silica gel assembly paste developed for assembly and easy disassembly all kinds of machine parts.

Eurol Assembly Paste HT/FD is suitable for treating and sealing of all type of screw / thread and non thread connections in:

- Brakes
- Exhaust systems
- Turbo chargers
- Steel mills and other high temperature areas
- Bakery ovens
- Refineries
- Cement mills
- Off road / agricultural machines
- Beverage industry
- Ship building and repair
- Chemical industry

Instructions for use:

- Clean the system thoroughly with Eurol Swift Clean 120 FD Spray
- Apply a thin layer
- Shake aerosol before use

Eurol Assembly Paste HT/FD Spray 400ML has the following characteristics:

- InS H1, 1797566
- Excellent protection against fretting corrosion
- Very oxidation stable
- Resistant to hot and cold water
- Resistant to most acids
- For very high temperatures up to +1400°C
- Contains solid lubricants
- Metal free
- For ferrous and non ferrous metals
- Low friction coefficient
- Very economical in use

Physical properties:

Colour	White	
NLGI consistency	2	ASTM D 217
Operating temperature	-30 - 1400 °C	

Version 1.0, 25-02-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com