

specialty lubricants

Eurol Assembly Paste HT/FD

Food grade assembly paste

Description

Eurol Assembly Paste HT/FD with SYNGIS Technology is a high temperature silica gel assembly paste developed for the assembly and easy disassembly of all kinds of machine parts.

Eurol Assembly Paste HT/FD is suitable for treating and sealing of all type of screw, thread and non-thread connections in brakes, exhaust systems, turbo chargers, steel mills, bakery ovens, refineries, cement mills, off-road and agricultural machines, the beverage industry, ship building and repair and the chemical industry.

Eurol Assembly Paste HT/FD is food grade InS H1 / NSF H1 certified, making it suitable for incidental food contact in, among others, the food industry, pharmaceutical industry, food service and agriculture.

Instructions for use

Clean the system thoroughly with Eurol Swift Clean 120 FD Spray Apply a thin layer with a brush

Eurol Assembly Paste HT/FD has the following characteristics

NSF H1, 161485 Excellent protection against fretting corrosion Very oxidation stable Resistant to hot and cold water Resistant to most acids For very high temperatures up to +1400°C Contains solid lubricants Metal free For ferrous and non ferrous metals Low friction coefficient Very economical in use

Physical properties

Colour	white	
NLGI consistency	2	ASTM D 217
Operating temperature	-30 - 1400	°C

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturers instructions.