



specialty lubricants



Quality is in our nature

Eurol Grease CS-2/103-S

Lubrication grease / anti corrosion agent

Description:

Eurol Grease CS-2/103-S with a high dose of Eurol SYNGIS Technology is a high performance lubricating grease developed for extreme situations in e.g. the paper, cement and steel industry and heavy equipment in offshore and shipping.

Eurol Grease CS-2/103-S is suitable for lubrication of:

- Open and closed bearings
- Cables and chains
- Autoclaves
- Steam valves
- Agricultural and fishing equipment
- Equipment working in extreme environments like (salt) water and high temperatures

Instructions for use:

- Clean the system thoroughly with Eurol Swift Clean 110 Spray
- Suitable for automatic lubrication systems

Eurol Grease CS-2/103-S has the following characteristics:

- Unique anti wear and EP properties
- Extreme protection against corrosion
- Shear stable
- Excellent water resistancy
- Resistant to shock loads
- Very good thermal and oxidation stability
- Less oil bleeding, so very suitable for automatic lubrication systems
- Low friction coefficient
- Lowers energy consumption
- Economical in use

Physical properties:

Colour	Brown	
NLGI consistency	2	ASTM D 217
Thickener type	Syngis	
Base oil viscosity	220 cSt	ASTM D 445
Operating temperature	-30 - 150 °C	

Greases - S005109
Version 1.1, 09-08-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com