



tesa® 4329 PV1



Product Information

Flexible masking tape for spray painting

Product Features

- Good flexibility for masking of curves
- Good adhesion tack to various surfaces
- Paints and fillers adhere to the reverse side
- Temperature resistance up to 70 °C

Product Description

tesa® 4329 is a flexible masking tape based on a fine crepe paper backing and a natural rubber adhesive. It is suitable for lightly duty spray painting and general purpose masking applications. The natural rubber adhesive system features good adhesion and tack to multiple surfaces. The excellent adherence of fillers or paints (water- or solvent-based) to the reverse side of the tape prevents any kind of paint flaking. It has a temperature resistance up to 70 °C for subsequent oven-drying.

Application Fields

- Suited for painting and lacquering work
- Masking during spray painting with subsequent oven drying up to 70 °C / 1h

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 125 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----------|--------------------------|---------|
| • Easy to remove | Yes | • Temperature resistance | 70 °C |
| • Elongation at break | 10 % | • Tensile strength | 33 N/cm |
| • Hand tearability | very good | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 2.8 N/cm |
|---------|----------|



tesa[®] 4329 PV1

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04329>