



# tesa<sup>®</sup> 4848 PV0

## Product Information

Transparent surface protection film for large areas in automotive and paint applications

### Product Features

- The protective film is extensively resistant to various chemical influences, mechanical impacts, and humidity.
- The translucent backing prevents a darkroom effect when applied on windows and panes.
- It ensures easy, residue-free removal within four

weeks of application, even after UV exposure during outdoor usage.

- It protects delicate and valuable surfaces from dirt or damage during processing, storage, and installation.

tesa<sup>®</sup> 4848PV0 features an environmentally friendly polyethylene (PE) backing in translucent red and a light, age-resistant acrylic adhesive.

The protection film tesa<sup>®</sup> 4848PV0 is especially suitable for longer-term, large area protection, interior as well as exterior, during paint-, plaster/stucco- or facade work.

### Application Fields

- Temporary Surface Protection

### Product Construction

- |                    |         |                    |         |
|--------------------|---------|--------------------|---------|
| • Type of adhesive | acrylic | • Backing material | PE film |
| • Total thickness  | 50 µm   |                    |         |

### Product Properties/Performance Values

- |                    |         |                  |     |
|--------------------|---------|------------------|-----|
| • Tensile strength | 12 N/cm | • Easy to remove | Yes |
|--------------------|---------|------------------|-----|



# tesa<sup>®</sup> 4848 PVO

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=04848>